

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S1	529	(257/680).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/01/26 17:39
S2	2123	(257/678).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/01/26 17:39
S3	5928	(257/678,680,690,692,711,727,731,733).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/01/31 18:36
S4	7	S3 and (octogan (eight near (face angle side)))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/01/26 17:43
S5	1	("20050098864").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/01/26 17:43
S6	3	S3 and (octogan (eight near (face angle side))) and (post stud pin)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/01/26 17:51
S7	2533	S3 and (post stud pin)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/01/26 17:51
S8	875	S3 and (post stud pin) and (optic\$3 image light transparent)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/01/26 17:52
S9	5937	(257/678,680,690,692,711,727,731,733).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/01/31 18:36
S10	471	S9 and (image light sensor) and transparent	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/01 11:28
S11	5937	(257/678,680,690,692,711,727,731,733).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/01 17:16

S12	90	S11 and (image light sensor) and transparent and post	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/01 13:39
S13	587	S11 and post	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/01 16:15
S14	2217	S11 and (post stud bump)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/01 13:45
S15	1	("6,759,723").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/01 16:16
S16	331	S11 and (post pedestal pillar edge adj member) and (image light sensor)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/01 17:17
S17	114	S11 and (post pedestal pillar edge adj member) and (image light sensor) and transparent	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/01 17:37
S18	3331	(438/15,106,115,116).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/01 17:37
S19	82	S18 and (image sensor light) and transparent and (post pillar pedestal edge adj member stud)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/01 17:41